



Model	OD43VS	OD50VS	OD55VS	OD65VS
Panel Size	43"	50"	55"	65"
Panel Resolution	1080 x 1920	2160 x 3840	2160 x 3840	2160 x 3840
Decoding Resolution	FHD	2K / 4K	2K / 4K	2K / 4K
Aspect Ratio	9:16	9:16	9:16	9:16
Brightness	450cd/m2	500cd/m2	550cd/m2	550cd/m2
Contrast Ratio	2000:1	2000:1	2000:1	3000:1
Panel Backlight	ELED			
Viewing Angle	178 degree			
Display Color	16.7 million			
Response Time	8 ms			
Orientation	Vertical			
Operating Duration	24 x 7			
Life Span	>50,000 hrs			
Speaker	2 x 10W Stereo			
Audio Output	3.5 mm Stereo Mini Jack			
Touch	-			
OS	Android			
Screen Protection	Fully Toughened Glass			
Ram	2G / 4G -8G Optional			
Storage	32G/64G - 128G Optional			
WiFi	2.4G / 5G Wi-Fi and Wi-Fi 802.11b / g / n protocols			
RJ45	1			
Bluetooth	Bluetooth 4.2			
4G Connectivity	Optional			
USB 2.0	2			
Audio Format	MP3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP			
Video Format	MP4, H.264, H.263, VP8, MAV, WMV, AVS			
Image Format	JPG, BMP, PNG			
Connectivity	USB / Mobile Application / Cloud (Optional)			
Power Supply	210-240V AC, 50/60 Hz			
Working Temperature	0 to 60 degree			
Storage Temperature	15 to 45 degree			
Storage Humidity	10% - 90% RH			
Power Consumption	<90 W	<110 W	<130 W	< 160 W
Display Screen Size (mm)	529 x 941	603 x 1073	680 x 1209	803 x 1428
Product Size (mm)	572 x 1736	646 x 1756	723 x 1776	846 x 1946
Gross Weight (kg)	43	46	48	62

Images displayed are for illustrative purpose only, Specifications may change without prior notice.

Application: Airport, Railway Station, Shopping Mall, Retail Showroom, Theatre, Hotel Lobby, Restaurant, Hospital, School, University, Government Office and more.



OD LED is a manufacturer & supplier of LED Video Wall and Digital LED Screen

Digicorp Studios

4/17, Sidco Industrial Estate, North Phase, Chennai - 600098

Call: +91.77000 55000 / 90030 10590 | Web: www.odled.net